## PHANTOM EXTENDED WHEELBASE

## Technical specification



1990 mm / 78.3 in



Dimensions

Number of doors / seats 4 doors / 5 seats Vehicle length 6092 mm / 239.8 in 1990 mm / 78.3 in Vehicle width Vehicle height (unladen) 1640 mm / 64.6 in 3820 mm / 150.4 in Wheelbase Turning circle 14.0 m / 45.9 ft Track, front 1686 mm / 66.4 in Track, rear 1676 mm / 66.6 in 1509 mm / 59.4 in Width at shoulder height, front Width at shoulder height, rear 1431 mm / 56.3 in 1042 mm / 41.0 in Leg room, front Leg room, rear 1349 mm / 53.1 in Head room, front 1047 mm / 41.2 in Head room, rear 979 mm / 38.5 in Boot volume 460 ltr / 16.2 cu ft Fuel tank capacity 100 ltr / 26.4 US gal

Weight

Curb weight 2694 kg / 5940 lb Axle load ratio, rear (unladen) 50.20% 3171 kg / 6990 lb Gross vehicle weight Payload 431 kg / 950 lb Axle load limit, front 1490 kg / 3285 lb Axle load limit, rear 1801 kg / 3970 lb

Engine

Engine / cylinders / valves V / 12 / 48 Fuel management Direct injection Displacement 6749 cc / 412 cu in Stroke 84.6 mm / 3.33 in Bore 92.0 mm / 3.62 in Power output @ engine speed 453 bhp / 460 PS (DIN) / 338 kW @ 5350 rpm Max torque @ engine speed 720 Nm / 531 lb ft @ 3500 rpm Compression ratio / fuel type Premium unleaded\*





6092 mm / 239.8 in 3820 mm / 1504 in

Transmission

8HP70 Transmission type

Transmission ratios

1st / 2nd / 3rd / 4.714 / 3.143 / 2.106 4th / 5th / 6th 1.667 / 1.285 / 1.000 7th / 8th 0.839 / 0.667 Reverse 3 317 Final-drive ratio 3.154

Steering & brakes

Rack & pinion, speed-sensitive Steering type variable-rate power assistance

Steering wheel revolutionsl lock to lock

15.53:1 Steering ratio

Brakes front / diameter Ventilated disc / 374 mm / 14.7 in Brakes rear / diameter Ventilated disc / 370 mm / 14.6 in

3.3

Aerodynamics

Drag  $Cd \times A$ 1.05 m<sup>2</sup> / 11.27 ft<sup>2</sup>

Performance<sup>†</sup>

Top speed 150 mph / 240 km/h (governed) Acceleration 0-60 mph 5.8 sec

Acceleration 0-100 km/h 61 sec Acceleration 0-1000 m 25.6 sec

Fuel consumption (USA)<sup>††</sup>

City 11 19 Highway

Fuel consumption (Canada)

TBC City Highway TBC Combined TBC

Wheels<sup>‡</sup>

Tyre, front Goodyear EMT 255/50 R21 106W

Wheel size, front 8"x 21"

Goodyear EMT 285/45 R21 109W Tyre, rear

Wheel size, rear 9.5"x 21"

Filling capacities

Radiator incl heater 14 ltr / 14.8 quarts 8.5 ltr / 9.0 guarts Engine oil Transmission fluid / final-drive fluid Lifetime filling

Electric system

Battery capacity / installed position 90+70 Ah / boot Alternator output rating 2 x 180 A / 2520 W

\*The engine is designed for octane grade 95 fuel; however, it may be run on fuel with a minimum octane grade of 91.

<sup>†</sup>Manufacturer's test results. Actual acceleration results may vary depending on specifications of the vehicle, road and environmental conditions, testing procedures and driving styles. These results should be used for comparison only and verification should not be attempted on public roads.

††EPA (Preliminary) – Use estimated mpg for comparison with other cars. Your mileage may vary with options, driving conditions, driving habits, the car's condition, speed and trip length. Actual highway mileage will probably be less.

<sup>‡</sup>With run-flat tyres, you can continue for a distance of at least 100 miles at speeds up to 50 mph, however, when notified you should check your tyre condition at the next available opportunity. The Goodyear Extended Mobility Tyre system (EMT) has run-flat capabilities.